

UNIVERSAL QUOTE FORM

Place your letterhead here and have the supplier of a rubberized surface submit on this form to allow for true comparison

Quotation For Rubberized 'Protective' Surface

Date: _____

Proponents must submit **Critical Height testing for a minimum of 4.25M (14')**

Proponents are asked to fill in the appropriate locations confirming compliance and/or conformance to the statement and the cost of the work described.

Excavation of existing play area	\$ _____
Preparation and installation of: - compacted granular base	\$ _____
- new curbing	\$ _____

Supply and installation of the rubberized play surface for a performance criteria of $G_{max} \leq 100$ and $HIC \leq 570$ for structures for under 5 year and $G_{max} \leq 125$ and $HIC \leq 700$ for structure 5-12 years and tested from the maximum accessible points (i.e. tops of railings) when site tested 10 to 25 days after installation, using the field test method of the ASTM F1292-09. Approximate total area _____ M²

\$ _____

Total cost of surface and base before taxes \$ _____

hst \$ _____

Total cost \$ _____

Colour of the Rubberized Surface to be installed _____

The rubberized surface installed under this quotation will be warranted for a period of 5 years for materials and workmanship and covers the surface for wear through, cracking, deterioration and that the maintained surface will remain resilient for the warranty period to provide for the performance required by the CSA Z614-07 and ASTM F1292 for the drop heights and locations initially tested in the temperature range of -5° to 49° C in a dry condition. Test to be performed with a free fall hemispherical triaxial headform. Damage as a result of vandalism will not be covered.

The rubberized surface installer will provide a certificate from the manufacturer of the polyurethane binders stating that the binders employed are suitable for the application of playground surfacing and will remain stable and resilient for the warranty period and that the binder is UV resistant.

The rubberized surface installer will provide a certificate that the installed surface meets the dimensional requirements of the CSA Z614-07 Standard for Playspaces for protective surfaces.

The rubberized surface installer will provide a maintenance procedure for the installed surface.

Quotation valid for _____ days

Signature _____, Name: _____ Title: _____

Company _____

Address _____ City _____ Prov. _____

Postal _____ Phone _____ Fax _____

Email _____